

RECEIVED  
CENTRAL FAX CENTER

Serial No.: 10/564,987

FEB 22, 2011

PF030118

Listing and Amendments to the Claims

Please **rewrite** claims 10 and 13 as indicated. Please cancel claim 12.

1-9. (Cancelled).

10. (Currently Amended) An illuminating device comprising an optical source emitting an unpolarized light beam having a divergence greater than or equal to  $5^{\circ}$  on either side of the average direction of said beam, a polarizing beam splitter included between first faces of a first and of a second transparent prism, which prisms each have a second exit face both situated within one and the same plane, said first faces and second faces of each prism being perpendicular; the unpolarized light beam penetrating into the first prism through a third face of this first prism and reaching the polarizing beam splitter that transmits the light with a first polarization direction and that reflects the light with a second polarization direction; the light transmitted by the polarizing beam splitter being transmitted to a third face of the second prism that reflects it toward said second exit face of the second prism, and the light reflected by the polarizing beam splitter being transmitted to said third face of the first prism that reflects it toward said second exit face of the first prism,

wherein said illuminating device also comprises a polarization rotator device associated with only one of said second exit faces of the prisms, a light integrating device, and a spatial light modulator of a liquid crystal type,

wherein said light integrating device has one entry face that is optically coupled to said second exit faces of the prisms and has one exit face, different from the entry face that is optically coupled with a liquid crystal layer of said spatial light modulator, wherein said light integrating device, when receiving the beams reflected by the third faces of the prisms through said entry face, delivers a beam through said exit face such that illumination of said exit face is substantially homogeneous over this exit face such as to illuminate

Serial No.: 10/564,987

PF030118

through said exit face the liquid crystal layer of said spatial light modulator in a uniform manner, and

wherein the polarizing beam splitter comprises a grid polarizer situated between the first faces of the first and of the second prism, and

wherein said illuminating device also comprises means for focusing the light beam emitted by the optical source close to the entry face of the integrator device.

11. (Previously Presented) The illuminating device as claimed in claim 10, wherein non-right angles of the prisms are substantially equal to  $60^\circ$  opposite the first faces and to  $30^\circ$  opposite the second face, and in that the average direction of said light beam is substantially perpendicular to the third face of the first prism as it penetrates into this prism.
12. (Cancelled).
13. (Currently Amended) The device as claimed in claim 10-12, wherein the divergence of said light beam is less than or equal to  $10^\circ$  on either side of the average direction of said beam.
14. (Cancelled).
15. (Previously Presented) The illuminating device as claimed in claim 10, wherein said grid polarizer is formed on the first face of the first prism or on the first face of the second prism.
16. (Previously Presented) The illuminating device as claimed in claim 15, wherein an air gap is provided between, on the one hand, the grid polarizer and said first face of the first or of the second prism on which it is formed and, on the

Serial No.: 10/564,987

PF030118

other, the other first face of the second or of the first prism, respectively, situated facing it.

17. (Previously Presented) The illuminating device as claimed in claim 10, wherein the index of the material of the prisms is less than or equal to 1.5.